



RENAULT SANDERO STEPWAY



TECHNICAL SPECIFICATIONS

	AUTHENTIQUE	UNITED	CUP	STEPWAY
SEATING CAPACITY	5	5	5	5
ENGINE	1.4 8V	1.6 8V	1.6 8V	1.6 8V
Fuel injection type	Multipoint (Mpi)	Multipoint (Mpi)	Multipoint (Mpi)	Multipoint (Mpi)
Cylinders	4	4	4	4
Displacement (cc)	1390	1598	1598	1598
Power (kW @ rpm)	55 @ 5 500	64 @ 5 500	64 @ 5 500	64 @ 5 500
Torque (NM @ rpm)	112 @ 3 000	128 @ 3 000	128 @ 3 000	128 @ 3 000
Bore x stroke (mm)	79.5 x 70	79.5 x 80.5	79.5 x 80.5	79.5 x 80.5
Compression ratio	9.5:1	9.5:1	9.5:1	9.5:1
Emissions control	Euro 3	Euro 3	Euro 3	Euro 3
Fuel requirement - petrol	Unleaded	Unleaded	Unleaded	Unleaded
TRANSMISSION				
Number of forward gears	5 speed	5 speed	5 speed	5 speed
STEERING				
Power assisted - hydraulic	Standard	Standard	Standard	Standard
Turning circle (m) - Kerb to Kerb	10.5	10.5	10.5	10.5
Turns - lock to lock	3.2	3.2	3.2	3.2
PERFORMANCE				
Acceleration: 0 - 100 km/h (secs)	13.0	11.5	11.5	11.5
Maximum speed (km/h)	161	175	175	175
AERODYNAMICS				
Drag coefficient (Cx)	0.36	0.36	0.36	0.36
SUSPENSION				
Front: MacPherson strut with wishbone arm	standard	standard	standard	standard
Rear: H-type torsion beam with programmed deflection and coil springs	standard	standard	standard	standard
FUEL CONSUMPTION				
Litres /100 km (Urban cycle)	9.6	10.0	10.0	10.0
Litres /100 km (Extra-urban cycle)	5.4	5.6	5.6	5.6
Litres /100 km (Combined cycle)	7.0	7.2	7.2	7.2
CO2 emissions (g/km)	164	170	170	183
Fuel tank capacity (litres)	50	50	50	50
WEIGHTS & DIMENSIONS				
Tare mass (kg)	1048	1048	1048	1048
Kerb mass (kg)	1013	1013	1013	1013
Wheelbase (mm)	2588	2588	2588	2588
Overall length (mm)	4020	4020	4020	4024
Overall width / with door mirrors (mm)	1746 / 1990	1746 / 1990	1746 / 1990	1753 / 1997
Overall height (mm)	1534	1534	1534	1564
Ground clearance (mm)	155	155	155	175
Front shoulder room - width (mm)	1388	1388	1388	1388
Rear shoulder room - width (mm)	1400	1400	1400	1400
Rear head room (mm)	878	878	878	878
BRAKES				
Bosch 8.0 system Anti-lock Brakes	Not available	Standard	Standard	Standard
EBD (Electronic Brake-Force Distribution)	Not available	Standard	Standard	Standard
Emergency Brake Assist (EBA)	Not available	Standard	Standard	Standard
Front: 2 discs	Standard	Standard	Standard	Standard
Rear: 2 drums	Standard	Standard	Standard	Standard
WHEELS & TYRES				
Wheels size	5.5 J14	5.5 J14	5.5 J15	5.5 J16
Wheels type	Steel with full covers	Steel with full covers	Alloy	Alloy
Tyres	185/70/R14 88T	185/70/R14 88T	185/65/R15 92T	195/55/R16 87H
Spare wheel	14" steel (normal size)	14" steel (normal size)	14" steel (normal size)	14" steel (normal size)
WARRANTY / SERVICE / MAINTENANCE				
5 Year / 150 000 km mechanical warranty	Standard	Standard	Standard	Standard
6 Year anti-corrosion warranty	Standard	Standard	Standard	Standard
15 000 km service intervals	Standard	Standard	Standard	Standard
3 Year / 45 000 km service plan	Optional*	Standard	Standard	Standard

* 3 year / 45 000 km Service Plan optional on 1.4 Authentique